


BRICK



The Brick is a **regular, rectangular paving stone with smooth surface and beveled edges**. A simple design makes it extremely **practical** and easy to be installed, so it becomes a universal tool in the hands of each paver. The Brick has a **very wide range of applications** – it is ideal for sidewalks, driveways, parking lots and bike paths.



USAGE

Thickness 4: Alleys and garden paths (pedestrian traffic only).

Thickness 6: Terraces, alleys and garden paths, walkways, patios, passages, driveways and car parks loaded with vehicle traffic up to 3.5 t.

Thickness 8: Terraces, alleys and garden paths, walkways, patios, passages, driveways and car parks for cars and trucks over 3.5 t, roads with low heavy traffic (KR3).

USEFUL RECOMMENDATIONS

Thickness 4: Installation in accordance with the construction practice. Do not use on roads used by vehicles or with high pedestrian traffic. Joint width 3-5 mm.

Thickness 6: Installation in accordance with the construction practice. Do not use on roads used by vehicles of more than 3.5 T. Use with a traffic load of up to 3.5 T is subject to the roadbase being constructed in accordance with the manufacturer's guidelines contained in the product documentation. Joint width 3-5 mm.

Thickness 8: Installation in accordance with the construction practice. Use with a traffic load of more than 3.5 t and heavy traffic KR3 is subject to the roadbase being constructed in accordance with the manufacturer's guidelines contained in the product documentation. Joint width 3-5 mm.

SPECIAL FEATURES

Thickness 4 cm, 6 cm, 8 cm: It is rectangular paving with a flat surface. The face surface is flat, classically beveled. Spacers of classic size. The pattern consists of one repetitive element. The stones made with the use of the two-ply technology.

DANE TECHNICZNE

Paving stones' thickness (cm)	4 cm, 6 cm, 8 cm
Pallet weight (kg)	4 cm i 6 cm: 1380 kg* ; 8 cm: 1520 kg*
Number of m2 on a pallet	4 cm -15 m2; 6 cm- 10,8 m2; 8 cm-8,64 m2

WZORNIK

STANDARD SURFACE*



graphite

grey

red

*The brick with the thickness of 4 cm (with the beveled edges) and 8 cm (without beveled edges): products on order.



Zobacz ten produkt online w swoim smartfonie

All surfaces should be executed in accordance with the guidelines of GDDKiA (General Directorate for National Roads and Motorways) No. D-05.03.23.